

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

1 Identification

- **Product identifier**
- **Trade name:** *Armor Crack Mender B*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Concrete Polishing Solutions
184 Cedar Place
Norris, TN 37828
www.go2cps.com
1 (877) 472-8200
- **Information department:** *Product safety department*
- **Emergency telephone number:**
Infotech (24 Hours) USA 1-800-535-5053 / International 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS OR DANGEROUS GOODS INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Solvent naphtha (petroleum), heavy arom. naphthalene
- **Hazard statements**
Combustible liquid.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.
- **Precautionary statements**
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: **Armor Crack Mender B**

(Contd. of page 1)

Keep away from flames and hot surfaces. – No smoking.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Immediately call a poison center/doctor.
 Do NOT induce vomiting.
 IF exposed or concerned: Get medical advice/attention.
 In case of fire: Use for extinction: CO2, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

64742-94-5	Solvent naphtha (petroleum), heavy arom.	50-100%
91-20-3	naphthalene	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: *Armor Crack Mender B*

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
91-20-3	naphthalene	15 ppm
· PAC-2:		
91-20-3	naphthalene	83 ppm
· PAC-3:		
91-20-3	naphthalene	500 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: *Armor Crack Mender B*

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

91-20-3 naphthalene

PEL Long-term value: 50 mg/m³, 10 ppm

REL Short-term value: 75 mg/m³, 15 ppm

Long-term value: 50 mg/m³, 10 ppm

TLV Long-term value: 52 mg/m³, 10 ppm

Skin; BEI

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Color: Colorless
Odor: Mild

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: *Armor Crack Mender B*

(Contd. of page 4)

· Odor threshold:	<i>Not determined.</i>
· pH-value:	<i>Not determined.</i>
· Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>218 °C (424.4 °F)</i>
· Flash point:	<i>79 °C (174.2 °F)</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Ignition temperature:	<i>540 °C (1,004 °F)</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Not determined.</i>
· Explosion limits:	
Lower:	<i>0.9 Vol %</i>
Upper:	<i>5.9 Vol %</i>
· Vapor pressure at 20 °C (68 °F):	<i>0 hPa (0 mm Hg)</i>
· Density:	<i>Not determined.</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
VOC content:	<i>0.00 %</i> <i>0.0 g/l / 0.00 lb/gal</i>
Solids content:	<i>2.5-10 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: *Armor Crack Mender B*

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	4,900-19,600 mg/kg (rat)
Dermal	LD50	50,000-200,000 mg/kg (rat)

91-20-3 naphthalene

Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

91-20-3	naphthalene	2B
---------	-------------	----

- **NTP (National Toxicology Program)**

91-20-3	naphthalene	R
---------	-------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022


Trade name: *Armor Crack Mender B*

(Contd. of page 6)

13 Disposal considerations

- *Waste treatment methods*
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- *Uncleaned packagings:*
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · <i>UN-Number</i> · <i>DOT</i> · <i>IMDG, IATA</i> | <p style="text-align: right;"><i>not regulated</i></p> <p style="text-align: right;">UN3082</p> |
| <ul style="list-style-type: none"> · <i>UN proper shipping name</i> · <i>DOT</i> · <i>IMDG</i> · <i>IATA</i> | <p style="text-align: right;"><i>not regulated</i></p> <p style="text-align: right;">ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NAPHTHALENE, CRUDE), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NAPHTHALENE, CRUDE)</p> |
| <ul style="list-style-type: none"> · <i>Transport hazard class(es)</i> · <i>DOT</i> · <i>Class</i> | <p style="text-align: right;"><i>not regulated</i></p> |
| <ul style="list-style-type: none"> · <i>IMDG, IATA</i> <div style="text-align: center;">  </div> | <p style="text-align: right;">9 Miscellaneous dangerous substances and articles</p> <p style="text-align: right;">9</p> |
| <ul style="list-style-type: none"> · <i>Class</i> · <i>Label</i> | <p style="text-align: right;"><i>not regulated</i></p> <p style="text-align: right;">III</p> |
| <ul style="list-style-type: none"> · <i>Packing group</i> · <i>DOT</i> · <i>IMDG, IATA</i> | <p style="text-align: right;"><i>not regulated</i></p> <p style="text-align: right;">III</p> |
| <ul style="list-style-type: none"> · <i>Environmental hazards:</i> · <i>Marine pollutant:</i> · <i>Special marking (IATA):</i> | <p style="text-align: right;">Product contains environmentally hazardous substances:
naphthalene</p> <p style="text-align: right;">Symbol (fish and tree)</p> <p style="text-align: right;">Symbol (fish and tree)</p> |
| <ul style="list-style-type: none"> · <i>Special precautions for user</i> · <i>Danger code (Kemler):</i> · <i>EMS Number:</i> · <i>Stowage Category</i> | <p style="text-align: right;">Warning: Miscellaneous dangerous substances and articles</p> <p style="text-align: right;">90</p> <p style="text-align: right;">F-A,S-F</p> <p style="text-align: right;">A</p> |
| <ul style="list-style-type: none"> · <i>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</i> | <p style="text-align: right;"><i>Not applicable.</i></p> |

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: *Armor Crack Mender B*

(Contd. of page 7)

· **Transport/Additional information:**

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCES, LIQUID, N.O.S. (NAPHTHALENE, CRUDE),
9, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

91-20-3 | naphthalene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

91-20-3 | naphthalene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

91-20-3 | naphthalene

C, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

91-20-3 | naphthalene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: **Armor Crack Mender B**

(Contd. of page 8)

- **Hazard pictograms**



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

*Solvent naphtha (petroleum), heavy arom.
naphthalene*

- **Hazard statements**

*Combustible liquid.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.*

- **Precautionary statements**

*If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
IF exposed or concerned: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Environment protection department.*

- **Contact:** *Mr. Swanson*

- **Date of preparation / last revision** *02/09/2022 / -*

- **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic*

(Contd. on page 10)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Crack Mender B

(Contd. of page 9)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Carc. 2: Carcinogenicity – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

US