Printing date 02/09/2022

Reviewed on 02/09/2022

1 Identification

- · Product identifier
- · Trade name: Armor Spall & Grout A
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Concrete Polishing Solutions

184 Cedar Place

Norris. TN 37828

www.go2cps.com

1 (877) 472-8200

- · Information department: Product safety department
- · Emergency telephone number:

Infotech (24 Hours) USA 1-800-535-5053 / International 1-352-323-3500 USE ONLY FOR HAZARDOUS MATERIALS OR DANGEROUS GOODS INCIDENT - SPILLS, LEAKS, FIRE, EXPOSURE, OR ACCIDENT CN109479

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate diphenylmethanediisocyanate,isomeres and homologues methylenediphenyl diisocyanate

(Contd. on page 2)

Trade name: Armor Spall & Grout A

(Contd. of page 1)

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2

Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
101-68-8	4,4'-methylenediphenyl diisocyanate	25-50%
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	25-50%
26447-40-5	methylenediphenyl diisocyanate	2.5-5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1</i> :		
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	0.15 mg/m
26447-40-5	methylenediphenyl diisocyanate	29 mg/m³
PAC-2:		
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	3.6 mg/m
26447-40-5	methylenediphenyl diisocyanate	40 mg/m³
PAC-3:		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	22 mg/m³
26447-40-5	methylenediphenyl diisocyanate	240 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm

*10-min

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Liquid

Color:

Dark brown

· Odor: · Odor threshold: musty, slight odour

Not determined.

· pH-value:

Not determined.

(Contd. on page 6)

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

		(Contd. of page
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	190 °C (374 °F)	
Flash point:	>110 °C (>230 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	400 °C (752 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	0 hPa (0 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	50-100 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 02/09/2022 Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

ATE (Acu	te Toxicity	Estimate)	
Oral	LD50	4,400-8,800 mg/kg (mouse)	
Inhalative	LC50/4 h	10.5-21 mg/l	

101-68-8 4,4'-methylenediphenyl diisocyanate 2,200 mg/kg (mouse)

LD50 Oral

- Primary irritant effect: on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories

101-68-8	4,4'-methylenediphenyl diisocyanate	
	diphenylmethanediisocyanate, isomeres and homologues	3

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

Printing date 02/09/2022 Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

· Other adverse effects No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

14 Transport information

· Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	

Not applicable.

Not applicable.

not regulated

15 Regulatory information

· UN "Model Regulation":

· Special precautions for user

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

	(Contd. of page 8)
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	Y .
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories

EPA (Environmental Protection Agency)		
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	CBD

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 (

SHSOR

· Signal word Danger

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate diphenylmethanediisocyanate,isomeres and homologues methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

(Contd. on page 10)

Printing date 02/09/2022

Reviewed on 02/09/2022

Trade name: Armor Spall & Grout A

(Contd. of page 9)

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Swanson
- Date of preparation / last revision 02/09/2022 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit, 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2